







FEATURES

8

=i=

-

Lightweight Module Design Designed for Helicopter Transport No Module Over 1100 lbs. Available HWL Chuck





Discovery I – Diamond Core Drill

DEPTH CAPA	CITIES: Based on max pullback & a 25% safety factor
В	2630 ft / 800 m
Ν	2000 ft / 605 m

PRIME MOVER	
Standard unit	Kubota V3800T, 4 cylinder, turbo charged diesel engine
Power:	99 HP @ 2600 RPM
Optional unit	Isuzu 4JJ1X, 4 cylinder, turbo charged diesel engine
Power:	131 HP @ 2500 RPM

ROTATION	UNI

Standard unit	300 drill head & chuck
Maximum opening:	2-3/16" (B size)
RPM:	1400 RPM
Torque:	1000 ft lbs
Chuck:	12,000 lbs capacity
Hydraulic motor:	Commercial gear - Bushing style
Gear ratios:	1 to 1
Optional unit	Boyles B15
Maximum opening:	3-1/2" (H size)
RPM:	1400 RPM
Torque:	1800 ft lbs
Chuck:	26,000 lbs capacity
Gear ratios:	3.1:1 & 4.4:1

FOUTCLAMP	
Standard unit	2 cylinder hydraulic open/close
Maximum opening:	3-1/2" (H size)
Optional unit	12HH 3-1/2" (H size)

MAST AND FEED	
Feed stroke:	72"
Pullback:	14,000 lbs
Pulldown:	7510 lbs
Drill angle:	45 to 90 degree
Tower:	10 ft or 20 ft rod pull capacity

WATER PUMP	
Standard unit	L0918B-CD (420) piston pump
Capacity:	24 GPM @ 700 PSI

Hydraulic motor direct drive
1000 ft of 3/16" cable

HYDRAULIC SYSTEM	
Controls:	Fully hydraulic, no electronics
Rod handling:	Sychronized chuck & footclamp w/ additional chuck control
System pressure:	3000 PSI
Filtration:	10 micron
Components:	Sauer Danfoss, Valvoil, Rexroth & Parker
Heat exchanger:	Water:oil

INCLUDED COMPONENTS
Mud mixer c/w whip lines
1000 ft of W/L cable
1 set of rod and casing jaws/bushings
55 gallon fuel tank
WEIGHT 4799 LBS

OPTIONS
Tracked carrier
Skid w/ stabilizer cylinders
Level wind winch
Diesel driven supply pump
Enclosed drill shack
Mud tank
French/Spanish labels & manual

PIONE Specialty & Multi-Purpose Air Rotary **Diamond Core** Seismic

MULTI POWER PRODUCTS LTD

975 CROWLEY AVENUE KELOWNA BC CANADA V1Y 9R6 P 250.860.6969 F 250.860.3340

MULTIPOWERPRODUCTS.COM

MULTI POWER

MULTIPOWERPRODUCTS.COM