

### L.A.D. - LIMITED ACCESS DRILL


Track Mounted Geotechnical and Environmental Drill











## L.A.D. - Limited Acccess Drill Track Mounted Geotechnical and Environmental Drill

# DEPTH CAPACITIES: Based on 300 CFM / 200 PSI compressor 4-1/2" Solid stem auger 200 ft / 60 m\* 6-5/8" Hollow stem auger 75 ft / 23 m\* 3-1/2" (89mm) Air rotary drilling 300 ft / 100 m\* \*Depending on ground conditions

# PRIME MOVER Standard unit Kubota V1505T, 4 cylinder, turbo charged diesel engine Power: 44.2 HP @ 3000 RPM

TRACK & UNDERCARRIAGE PACKAGE		
Model:	Chermack 2B 60" track	
Design:	Compact, rubber track set	
Speed:	2.6 mph	
Stabilizers:	Four hydraulic stabilizers	

TOP DRIVE ROTATION UNIT		
Max torque:	2500 lbs /ft	
RPM:	0-95 RPM	
Spindle:	Floating w/ HD U-joint assembly 1-5/8" hex	
Rotation motor:	Char-Lynn 6K series	

MAST AND FEED	
Design:	Double rod cylinder and chain feed
Pullback:	12,500 lbs.
Pulldown:	12,500 lbs.
Feed stroke:	66" - Longer feed stroke option available
Working angle:	45 to 90 degree

HYDRAULIC SYSTEM	
Design:	Fully hydraulic, no electronics, open loops
Capacity:	20 GPM
System pressure:	3000 PSI
Filtration:	10 micron
Components:	Sauer Danfoss, Char-Lynn & Parker
Heat exchanger:	Air:oil

CONTROL PANEL		
Panel:	Feed, rotate, L&R track, SPT hammer control and setup functions	
Gauges:	Rotation, holdback & air pressure	
Opening:	6 - 1/4"	

FOOTCLAMP	
Design:	Two hydraulic cylinder & jaw / Bolt-on, removable design
Clamping Force:	20,000 lbs
Opening:	6 -1/4"

#### **DIMENSIONS (TRANSPORT)**

34" W x 115" L x 69" HT

#### WEIGHT 3500 LBS.

OPTIONS
SPT auto hammer
Diamond core package
Rotzler winch
RAB package
Telescoping tracks
Radio remote package for track drive
Water pump



### **MULTI POWER PRODUCTS LTD**

975 CROWLEY AVENUE KELOWNA BC CANADA V1Y 9R6 P 250.860.6969 F 250.860.3340

**MULTIPOWERPRODUCTS.COM** 

