

**PIONEER II**Diamond Core Drill

MULTI POWER



## Pioneer II - Diamond Core Drill

#### **DEPTH CAPACITIES:** Based on max pullback & a 25% safety factor

B 1230 ft / 373 m N 995 ft / 301 m

## **PRIME MOVER**

**Standard unit** Kubota V2403T, 4 cylinder, turbo charged diesel engine

**Power:** 59 HP @ 3000 RPM

#### **ROTATION UNIT**

Standard unit	Top drive c/w built in swivel
RPM:	1400 RPM
Torque:	1000 ft lbs
Hydraulic motor:	Commercial gear - Bushing style
Gear ratios:	1 to 1

#### **FOOTCLAMP**

Standard unit	2 cylinder hydraulic open/close
Maximum onening	3-1/2" (H size)

## **MAST AND FEED**

Feed stroke:	72"
Pullback:	6900 lbs
Pulldown:	3000 lbs
Drill angle:	45 to 90 degree
Tower:	5 ft. rod pull capacity
Mast dump:	Included

#### **WATER PUMP**

Standard unit E0413C FMC piston pump

Capacity: 25 GPM @ 550 PSI

## **WINCHES**

Wireline winch Hydraulic motor direct drive

Capacity: 1000 ft of 3/16" cable

## **HYDRAULIC SYSTEM**

Controls:	Fully hydraulic, no electronics
Rod handling:	Hydraulic footclamp
System pressure:	3000 PSI
Filtration:	10 micron
Components:	Sauer Danfoss, Valvoil, Rexroth & Parker
Heat exchanger:	Water oil

## **INCLUDED COMPONENTS**

Trailer package

Mud mixer c/w whip lines

1000 ft of W/L cable

1 set of rod and casing jaws/bushings

55 gallon fuel tank

## **WEIGHT 2995 LBS**

#### **OPTIONS**

Tracked carrier

Skid w/ stabilizer cylinders

Level wind winch

Diesel driven supply pump

Enclosed drill shack

Mud tank

French/Spanish labels & manual





# **MULTI POWER PRODUCTS LTD**

975 CROWLEY AVENUE KELOWNA BC CANADA V1Y 9R6 P 250.860.6969 F 250.860.3340

**MULTIPOWERPRODUCTS.COM** 

