



SCOUT TRACK

RUBBER TRACKED CARRIER

MULTI▶POWER



FEATURES

- Compact, lightweight and modular design
- Hydraulic lifting crane and (4) telescoping stabilizer jacks
- ST low impact. highspeed rubber track system
- Radio remote drive and winch system
- Optional Cat 305E steel track undercarriage

Scout Track - Rubber Tracked Carrier

SPECIFICATIONS

CAPACITY:

Machine payload:	3000 lbs.
Max crane pick weight:	3190 lbs.

PRIME MOVER

Standard unit	Kubota V1505T, 4 cylinder, turbo charged diesel engine
Power:	44.2 HP @ 3000 RPM

TRACK PACKAGE

Model:	MPP ST (Scout Track) undercarriage
Design:	Hyd. driven piston motors, low impact rubber track, 2 speed drive
Drive speed:	4 KM/HR
Ground pressure:	3 PSI
Optional:	Cat 305E steel tracks

HYDRAULIC CRANE:

Model:	Maxilift M180.3H
Lifting capacity:	1450 kg @ 1.2 meters & 420 kg @ 4 meters

RADIO REMOTE:

Model:	Miratron wireless remote package
Operation:	Control for LH track, RH track & winch in/out, & remote E-stop

WINCH:

Model:	Warn 6000 hydraulic winch c/w fairlead & tension kits
Capacity:	5/16" x 100 ft. cable

STABILIZER JACKS

Cylinder:	(4) Hydraulic stabilizer cylinders
Telescoping:	Front and rear sets of stabilizers telescope in and out of machine
Control:	(4) Hydraulic valve levers for each cylinder and (2) valve levers for telescoping

DECK

Capacity:	3000 lbs.
Size:	36" x 104" free deck space (125" L with end gates removed)
Construction:	Steel w/ welded D rings

HYDRAULIC SYSTEM

Main pump:	Sauer Danfoss LS/PC main pump (drive & winch)
Secondary pump:	Gear pump for crane and set-up functions
Filtration:	10 micron filtration
Control:	Saur Danfoss PVG32 LS/PC valve for drive & winch
Heat exchanger:	Air:oil

DIMENSIONS

56" W x 125" L

MACHINE WEIGHT (EMPTY) 3800 LBS.



Diamond Core



Seismic



Air Rotary



Specialty &
Multi-Purpose

MULTI POWER PRODUCTS LTD

975 CROWLEY AVENUE
KELOWNA BC CANADA
V1Y 9R6

P 250.860.6969
F 250.860.3340

MULTIPOWERPRODUCTS.COM

MULTI▶POWER

MULTIPOWERPRODUCTS.COM