



WATER PUMPS
Supply & Pressure Pumps

MULTI▶POWER



Water Pumps

SPECIFICATIONS

SUPPLY PUMPS

EO413C C/W YANMAR L100V SUPPLY PUMP

Prime mover:	Yanmar L100V 9.5HP diesel engine
Pump:	FMC EO413C upright piston pump
Flow Capacity:	21 GPM @ 600 PSI
Reduction:	Nord helical inline
Frame:	Steel, primed and painted
Weight:	508 lbs.
Dimensions:	43" L x 25" W x 41" HT
Accessories:	Tool storage, control panel, lifting points 12V battery, rubber motor mounts

W1122B-CD (435) C/W KUBOTA D1105 SUPPLY PUMP

Prime mover:	Kubota D1105 32HP diesel engine
Pump:	American AW1122B-CD (435) piston pump
Flow Capacity:	37 GPM @ 1000 PSI
Transmission:	Newage 40M Four speed w/ clutch assy.
Frame:	Steel, primed and painted
Weight:	1480 lbs.
Dimensions:	70" L x 32" W x 43" HT
Accessories:	Tool storage, control panel, lifting points 12V battery, rubber motor mounts

PRESSURE PUMPS

W1122B-CD (435) C/W HYDRAULIC MOTOR DRIVE

Prime mover:	Char-Lynn 2K series hydraulic motor
Pump:	American AW1122B-CD (435) piston pump
Flow Capacity:	37 GPM @ 1000 PSI
Coupling:	Direct mount
Frame:	Steel, primed and painted
Weight:	505 lbs.
Dimensions:	42" L x 32" W x 24" HT

L0918BCD (420) C/W HYDRAULIC MOTOR DRIVE

Prime mover:	Char-Lynn 2K series hydraulic motor
Pump:	FMC L0918BCD (420) piston pump
Flow Capacity:	20 GPM @ 700PSI
Coupling:	Direct mount
Frame:	Steel, primed and painted
Weight:	395 lbs.
Dimensions:	36" L x 32" W x 24" HT

A0413C C/W HYDRAULIC MOTOR DRIVE

Prime mover:	Char-Lynn H series hydraulic motor
Pump:	FMC A0413C 2 cylinder upright
Flow Capacity:	7 GPM @ 550 PSI
Coupling:	Direct mount
Frame:	Steel, primed and painted
Weight:	85 lbs
Dimensions:	24" L x 18" W x 20" HT



Diamond Core



Seismic



Air Rotary



Specialty &
Multi-Purpose

MULTI POWER PRODUCTS LTD

975 CROWLEY AVENUE
KELOWNA BC CANADA
V1Y 9R6

P 250.860.6969
F 250.860.3340

MULTIPOWERPRODUCTS.COM

MULTI▶POWER

MULTIPOWERPRODUCTS.COM